



# RUBBER-TRACK BRUSH & TREE ANNIHILATOR

***Compact, Light on Her Feet, Gentle Rubber Tracks, Awesome Power!***

**Watch this package in action** and you'll be amazed! It's hard to comprehend how such a compact, easy-to-maneuver machine can turn so much growth into mulch so fast.

**SEPPi M® cutting heads are simply state-of-the-art.** Stronger. Faster. More reliable. Easier to service. Superior to any other head on the market. Look close and you'll see engineering refinements competitors won't have for years. Choose from 6'7", 5'9" and 4'11" cutting widths. All are capable of continuous-duty cutting of 4" diameter material.

**TAKEUCHI® carrier is equally impressive.** 18" wide rubber tracks. Turbo-charged 100 h.p. diesel with joystick controlled hydrostatic drive. ROPS/FOPS tilt-back operator's compartment. Electrohydraulic push button auxiliary hydraulics. Planetary final drives with spring-applied, hydraulically-released disc brakes.



***Big jobs cut down to size  
in a BIG HURRY!***

**BRUSH  
TECHNOLOGY**

**[www.brush-technology.com](http://www.brush-technology.com)**

14375 James Road Rogers, MN 55374  
Phone: (763) 428-5099 Fax: 763-428-5051



**BEFORE**



**AFTER**

*No burning. No excavator. No dozer. No chemicals. Discharged material is easy to walk or drive on. It also helps soil retain moisture and minimize erosion.*



*Don't get lost in the woods without one! Cab is fully enclosed with wire mesh screen and windshield. Air conditioning and heater are available.*



*Quick-mounting bucket, sweeper and stump cutter are also available. ROPS/FOPS tilt-back operator's compartment for easy service access.*



*Compact and easy to maneuver. "Selectively clear" unwanted growth to within inches of larger trees, fencing, buildings and more.*

**SEMPI M® Specifications / Dimensions**

Cutting Width	Total Hammers	Cutter Head & Carrier			
		Weight	Length	Width	Height
4'-11"	24	12958	14'	5'-9"	88"
5'-9"	29	13255	14'	6'-9"	88"
6'-7"	33	13428	14'	7'-6"	88"

- Designed for continuous-duty cutting of 4" diameter standing or felled material.
- Heavy-duty shaft is electronically balanced for longer life and to minimize vibration.
- Hammer design is second to none for performance, longevity and ease of service.
- Ground pressure is approximately 5 psi.
- Easy access to all components simplifies maintenance.

**Takeuchi® TL-150 Rubber Track Loader**

- YANMAR 4 cyl., turbo-charged diesel — 101.5 h.p. @ 2,200, max. torque 291 ft. lbs @ 1,400.
- Low & high-range travel speed — 5.0 / 6.9 mph.
- Planetary final drives with spring-applied, hydraulically-released disc brakes.
- ROPS / FOPS tilt-back operator's compartment.
- Electrohydraulic push-button control of boom & arm float circuit and auxiliary hydraulics.
- Pilot-operated, joystick-controlled hydrostatic drive.
- Universal, quick-attach mounting brackets.
- Emergency engine shut-down system.
- Electronic engine monitoring system.
- 6-way suspension seat with retractable seat belt.
- Front and rear halogen work lights.

**BRUSH TECHNOLOGY**

**www.brush-technology.com**

14375 James Road Rogers, MN 55374  
 Phone: (763) 428-5099 Fax: 763-428-5051

*Features and specifications subject to change without notice.*

*Proudly distributed by*

